

PETROLEUM ETHER AR BOILING RANGE 60-80°C

PRODUCT CODE	605375
SYNONYMS	--
C.I. NO.	--
CASR NO.	8032-32-4
ATOMIC OR MOLECULAR FORMULA	--
ATOMIC OR MOLECULAR WEIGHT	--
PROPERTIES	--

PARAMETER	LIMIT
Description	A clear liquid, colour not more than 10 Hazen units with a characteristic odour.
Solubility	Miscible with methanol, benzene, ether.
Boiling range (60-80°C)	Min 95.0%
Wt. per ml at 20°C	0.660 - 0.680g
Bromine number	<3.0

MAXIMUM LIMIT OF IMPURITIES	
Water	0.015% w/v
Acidity	0.0013ml N% w/v
Non-volatile matter	0.001% w/v
Sulphur compounds (CS ₂)	0.0003% w/v
Copper (Cu)	0.0001% w/v
Iron (Fe)	0.0001% w/v
Lead (Pb)	0.0001% w/v

Note(s): Assay (if applicable) method mentioned.

DANGER HAZARD STATEMENTS: May cause respiratory irritation. Highly flammable liquid and vapour. Causes eye irritation. PRECAUTIONARY STATEMENTS : Prevention: Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Keep away from heat/sparks/open flame - No smoking. Keep container tightly closed. Wear protective gloves and eye/face protection. Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin or hair: remove/take off immediately all contaminated clothing. Rinse with water/shower. In case of fire, use foam for extinction. If eye irritation persists, get medical advice/attention.	IMDG Code : UN No. : IATA :
--	-----------------------------------

Disposal: -----

Hazard Pictogram(s) :-



GHS02



GHS07

Replace date 14-Aug-2026