



Product Specification

cdhfinechemical.com

SODIUM DIHYDRIDO-BIS-(2-METHOXYETHOXY) ALUMINATE -70% IN TOLUENE			
PRODUCT CODE	219505		
SYNONYMS	SBAH, sodium bis(2-methoxyethoxy)aluminium dihydride.		
C.I. NO.	-		
CASR NO.	22722-98-1		
ATOMIC OR MOLECULAR FORMULA	C ₆ H ₁₆ AlNaO ₄	Na+	H ₃ CO ^O AI ^O OCH ₃
ATOMIC OR MOLECULAR WEIGHT	202.16		ΎН́Η
PROPERTIES			
PARAMETER	LIMIT		
Description	Colourless to light yellow clear to slightly hazy viscous liquid	l.	
Solubility	Miscible with aromatic hydrocarbons, ether, tetrahydrofuran, dimethyl ether and dimethlyformamide.		
Assay	68.0 – 72.0% (w/w)		
Wt per ml at 25 ºC	About 1.036g		
Note(s) : Assay (if applicable) method mentio	ned.		
swallowed. May cause allergic or asthmatic symptom reaction . May be corrosive to metals. Causes severe PRECAUTIONARY STATEMENTS : Prevention : Do not breathe dust/fume/gas/mist/va Avoid breathing dust/fume/gas/mist/vapours/spray. hands thoroughly after handling. Wear protective glo inadequate ventilation wear respiratory protection. If workplace. Wear protective gloves/clothing and eye, Ground/bond container and receiving equipment. Us Take precautionary measures against static discharge heat/sparks/open flame - No smoking. Keep container protection. Response : In case of fire, use alcohol-type foam for INHALED: Remove to fresh air and keep at rest in a p remove/take off immediately all contaminated cloth respiratory symptoms call a POISON CENTER or doct skin irritation or rash occurs, seek medicaadvice/attee minutes. Remove contact lenses, if present and easy NOT induce vomiting. IF INHALED: If breathingis diffi comfortable for breathing. IF ON SKIN: Gently wash of CENTER or doctor/physician. Call a POISON CENTER or to Label or MSDS.	pours/spray. Use only outdoors or in a well ventilated area. Do not eat, drink or smoke when using this product. Wash oves/clothing.Do not breathe dust or mist.In case of Contaminated clothing should not be allowed out of the /face protection. Wash thoroughly after handling. se explosion-proof electrical/ventilating/lighting/equipment e Use only non-sparking tools. Keep away from er tightly closed. Wear protective gloves and eye/face extinction. Wash contaminated clothing before reuse. IF osition comfortable for breathing. If on skin or hair:	UN NG IATA	: 4.3(3)
Hazard pictogram(s) :	o cover spillage should be thoroughly washed with water bef	ore aispo	osal as normal waste.

